

13420 South Normandie Avenue Gardena, CA 90249 (310) 532-9737 (213) 770-0055

Fax: (310) 516-8203

Date: 4/30/98

Head CC

## CUSTOMER SPECIFICATIONS SAVE FOR REORDERING

Job Card #: 291043

Year

Customer: A	Customer: AH-836L		
7 T	Make	Model	
Engine Type:	HONDA	CB-750 SO	
Displacement:			
Bore:	2.559		
Stroke:			
Rod Length:			
Comp. Height:	0.940		
Compression:	10.50		
Pin Diameter:	0.591		
Top Groove:	0.040		
2nd Groove:	0.048		
Oil Groove:	0.110		
Piston Weight:	x 149	g.	

	Part Number	Qty
Pistons:	D/VR-2	20
	Part # AH-836L box in kit's	
Pins:	591 2050	20
Rings:	65.0 mm XC	20
Locks:	.591 + .040 CW	40
Buttons:		
GLS:		

## **INSTALLATION INSTRUCTIONS:**

ARIAS FORGED PISTONS ARE MANUFACTURED TO PROVIDE

PISTON TO CYLINDER WALL CLEARANCE AS INDICATED BELOW,

BASED ON BORE DIAMETER GIVEN AT TIME OF ORDER.


\*Clearance: 0.0010

Account #: ARIAS

Head

2-VALVE

Measure clearance at the bottom of the piston



\*NOTE: IF PISTONS ARE PRO-COATED, SUBTRACT .002 FROM CLEARANCE NUMBER.